

Extended Performance Report

Instrument: Instrument 1

Module	Type	Firmware rev.	Serial number
Capillary Electrophoresis	HPCE	2.3	
Diode array detector	79854C	1.3	
Analog/digital converter	35900	Rev E.01.02	

Software Revisions for:

- Acquisition: Rev. B.01.03 [204] Copyright © Agilent Technologies
- Data Analysis: Rev. B.04.03 [16] Copyright © Agilent Technologies

Analysis method:

Path: C:\CHEM32\1\METHODS\CE\CHARGED_ACIDS.M
Name: CHARGED_ACIDS.M


Sample information for Location: Vial 3


Sample Name:	sn02; ma00,1	Multiplier:	1.00
Injection#:	1	Dilution:	1.00

Acquisition information:

Operator: lida
Date/Time: 5/30/2013 1:59:55 PM
Data file:
Path: F:\OD LIDY\
Name: SN-MA00,1_1.D
Method file:
Path: C:\CHEM32\1\METHODS\CE\LIDA METODY\
Name: LIDA_11C.M

Signal description: ADC1 A, ADC CHANNEL A
ADC1 B, ADC CHANNEL B
DAD1 A, Sig=195,10 Ref=off
DAD1 B, Sig=210,5 Ref=off
DAD1 C, Sig=248,5 Ref=off






Compound# 8 : HVL
Amount [ng/ul]: 0.0000

Peak description [min]:

Signal: DAD1 B, Sig=210,5 Ref=off

MigTime: 8.995 k': -
Height: 10.82 Area: 171.7
Start: 8.415 End: 9.058
Skew: -0.65831 Excess: -0.32443
Width at half height: 0.26000
5 sigma: 0.57095
tangent: 0.33127
tailing: 0.56762
Symmetry: 19.47333
USP Tailing: 0.55831
Integration type: BV
Time increment [msec]: 100.0
Data points: 710



Statistical moments (BB peak detection):

M0: 172.2
M1: 8.832
M2: 0.016501
M3: -0.001395
M4: 0.000729
Tangent method
Halfwidth method
5 sigma method
Statistical

Efficiency: Plates per ..

capillary meter
11806 -
6636 -
6210 -
4727 -

Relationship to preceeding peak:

Resolution Tangent method: -
Halfwidth method -

Selectivity:

5 sigma method -
Statistical method -

#	Mig.Time [min]	Amount [ng/ul]	Name	Page #
1	8.995	0.0000	HVL	4
		=====		
Total:		0.0000		

*** End of Report ***