

Extended Performance Report

Instrument: Instrument 1

Module	Type	Firmware rev.	Serial number
Capillary Electrophoresis	HPCE	2.3	
Diode array detector	79854C	1.3	
Analog/digital converter	35900	Rev E.01.02	

Software Revisions for:

- Acquisition: Rev. B.01.03 [204] Copyright © Agilent Technologies
- Data Analysis: Rev. B.04.03 [16] Copyright © Agilent Technologies

Analysis method:

Path: C:\CHEM32\1\METHODS\CE\CHARGED_ACIDS.M
Name: CHARGED_ACIDS.M


Sample information for Location: Vial 3


Sample Name:	sn02; ma00,5	Multiplier:	1.00
Injection#:	1	Dilution:	1.00

Acquisition information:

Operator: lida
Date/Time: 5/31/2013 12:35:35 AM
Data file:
Path: F:\OD LIDY\
Name: SN-MA00,5_1.D
Method file:
Path: C:\CHEM32\1\METHODS\CE\LIDA METODY\
Name: LIDA_11K.M

Signal description: ADC1 A, ADC CHANNEL A
ADC1 B, ADC CHANNEL B
DAD1 A, Sig=195,10 Ref=off
DAD1 B, Sig=210,5 Ref=off
DAD1 C, Sig=248,5 Ref=off






Compound# 3 : HVL
Amount [ng/ul]: 0.0000

Peak description [min]:

Signal: DAD1 C, Sig=248,5 Ref=off

MigTime: 5.913 k': -
Height: 15.95 Area: 80.3
Start: 5.747 End: 5.977
Skew: -0.54755 Excess: -0.34521
Width at half height: 0.08250
5 sigma: 0.16250
tangent: 0.12047
tailing: 0.15833
Symmetry: 6.01650
USP Tailing: 0.57927
Integration type: BBA
Time increment [msec]: 100.0
Data points: 227



Statistical moments (BB peak detection):

M0: 80.3
M1: 5.875
M2: 0.001346
M3: -0.000027
M4: 4.80838e-006
Tangent method
Halfwidth method
5 sigma method
Statistical

Efficiency: Plates per ..

capillary meter
38576 -
28482 -
33129 -
25643 -

Relationship to preceeding peak:

Resolution Tangent method: -
Halfwidth method -

Selectivity:

5 sigma method -
Statistical method -

#	Mig.Time [min]	Amount [ng/ul]	Name	Page #
1	5.913	0.0000	HVL	4
		=====		
Total:		0.0000		

*** End of Report ***